17cm prime focus receiver, UBB (600-3000 MHz)

This is an ultra broad band (UBB) 2-channel system covering a range from 1200 to 3000 MHz. The band used to be 0.6 - 3.0 GHz, but that was changed due to RFI issues. Be aware that there is still a lot of RFI in the current frequency range. The system is mainly used for pulsar observations.

Calibration Information

Frequency [GHz]	Channel	Polarisation	Tcal [K]		Sensitivity [K/Jy]			TMB/S [K/Jy]	FWHM [arcsec]	Last update
0.85 (not available any more)	A+B	LCP+RCP	97.0	48	1.25	38	44		930	Sep 2012
1.4	A+B	LCP+RCP	188.0	56	1.25	45	44		650	Sep 2012
2.35	A+B	LCP+RCP	156.0	53	1.25	42	44		400	Sep 2012
normalized Gain curve (G = A0 + A1·Elv + A2·Elv2) Observed in confirmed										
A0 = 1.0	A	1 = 0.0	ŀ	42 = 0	0.0	Sep	2012			

Comments:

• Receiver has been modified in 2016 due to RFI issues. The frequency range was originally 0.6 - 3.0 GHz, now the lower band edge is as 1.2 GHz.

Version description for OBSINP

RX Name	Wavelength [cm]	Frequency (center) [GHz]	Nr. of Horns			
P170mm UBB (1.2-3 GHz)	25.0-10.0	1.2-3.0 (1.8)	1			
Version:	Comment					
1. Continuum/Line	Continuum and spectroscopy version					
2. Pulsar	Pulsar Version					
Horn offsets [arcsec]	0.0, 0.0					

Channel assignment in the MBFITS data files

Note that the narrow line and VLBA IF channels are usually only available when the specific line version of the receiver was selected. In addition for most receivers with narrow line channels the cables at the patch board need to be connected by the receiver group.

To select different channel numbers in OBSINP, the online plot, or the toolbox the numbers have to be specified like c(1)+c(2) to add channel 1 and 2. E.g. channel 1 and 2 contain the LCP and RCP broadband channels, then "OnIPlot pen='c(1)+c(2)'" or "toolbox use='c(1)+c(2)'" will select these channels. In OBSINP the pen can be directly specified in the receiver selection menu.

Abbreviations:

SB: narrow band channel (Schmalband-Kanal), 100 MHz band width BB: digital broad band channel (Breitband-Kanal), band width varies for different receivers VLBA: VLBA IF, 500 MHz band width optical: optical fibre with 4 GHz of band width BW: band width TP: total power

P170mm UBB (1.2-3 GHz)							
Channel	IF	Pol.	Comment				
1	optical	LCP	TP A				
2	optical	RCP	TP B				

Tcal and Tsys measurements

TODO

From: https://eff100mwiki.mpifr-bonn.mpg.de/ - Effelsberg 100m Teleskop

Permanent link: https://eff100mwiki.mpifr-bonn.mpg.de/doku.php?id=information_for_astronomers:rx:p170mm&rev=1481536959

Last update: 2016/12/12 11:02

