2.2cm/2.5cm prime focus receiver (12100-12280 MHz/12900-13600 MHz)

This is a 2-channel system used for spectroscopy. The 2.5cm part is realized by a new filter. The calibration parameters are still somewhat uncertain (about 10%). The lower part of the band at 12.1 GHz is affected by RFI from TV satellites which might also explain the higher Tsys.

Calibration Information

Frequency [GHz]	Channel	Polarisation	Tcal [K]	-	Sensitivity [K/Jy]	SEFD [Jy]	Aperture Eff. [%]	TMB/S [K/Jy]	Main Beam Eff. [%]	FWHM [arcsec]	Last update
12.10	A	LCP	6.5	128	1.4	93	48	1.9	71	65.0	Dec 2009
12.10	А	RCP	5.6	210	1.4	155	48	1.9	70	65.0	Dec 2009
12.18	A	LCP	5.2	79	1.4	57	47	1.9	75	65.0	Dec 2009
12.18	A	RCP	4.5	102	1.4	78	47	1.9	71	65.0	Dec 2009
13.09	A	LCP	2.0	64	1.45	44	51	1.9	78	62.0	Aug 2009
13.09	В	RCP	2.0	65	1.45	45	51	1.9	78	62.0	Aug 2009
13.39	A	LCP	1.8	61	1.4	42	50	1.9	74	59.3	Sep 2005
13.39	В	RCP	2.1	63	1.4	44	50	1.9	74	59.3	Sep 2005
normalized Gain curve (G = A0 + A1·Elv + A2·Elv2) Observed in confirmed							,				
A0 = 0.964	4 A1 =	2.1838E-03	A2	2 = -3	.3018E-05	Dec	2009				

Comments:

• The values across the band and for LCP and RCP do not differ significantly in the 2.2cm band.

Version description for OBSINP

RX Name	Wavelength [cm]	Frequency (center) [GHz]	Nr. of Horns		
P22mm 4-Box (12,1- 13,6 GHz)	2.2-2.5	12.1-13.6 (13.1)	1		
Version:	Comment				
1. Cont./Line: 12,1-12,25 GHz (2,5 cm) (BW: 100 MHz)	Continuum and spectroscopy at 2.5cm				
2. Cont./Line: 12,9-13,6 GHz (2,2 cm) (BW: 100 MHz)	Continuum and spectroscopy at 2.2cm				
Horn offsets [arcsec]	-1155.5, 1066.7				

Channel assignment in the MBFITS data files

Note that the narrow line and VLBA IF channels are usually only available when the specific line version of the receiver was selected. In addition for most receivers with narrow line channels the cables at the patch board need to be connected by the receiver group.

To select different channel numbers in OBSINP, the online plot, or the toolbox the numbers have to be specified like c(1)+c(2) to add channel 1 and 2. E.g. channel 1 and 2 contain the LCP and RCP broadband channels, then "OnIPlot pen='c(1)+c(2)'" or "toolbox use='c(1)+c(2)'" will select these channels. In OBSINP the pen can be directly specified in the receiver selection menu.

Abbreviations:

SB: narrow band channel (Schmalband-Kanal), 100 MHz band width BB: digital broad band channel (Breitband-Kanal), band width varies for different receivers VLBA: VLBA IF, 500 MHz band width BW: band width TP: total power

2.2cm/2.5cm PFK (Multi-RX-Box II)						
Channel	IF	Pol.	Comment			
1	SB	LCP	2.2cm, TP A			
2	SB	RCP	2.2cm, TP B			
3	SB	cross	2.2cm, cos AB			
4	SB	cross	2.2cm, sin AB			
5	SB	LCP	2.5cm, TP A			
6	SB	RCP	2.5cm, TP B			

Tcal and Tsys measurements

TODO

From:

https://eff100mwiki.mpifr-bonn.mpg.de/ - Effelsberg 100m Teleskop

Permanent link:

https://eff100mwiki.mpifr-bonn.mpg.de/doku.php?id=information_for_astronomers:rx:p22mm&rev=1363093605



Last update: 2013/09/30 12:07